

# GLUE-LESS CONDUIT FITTINGS

## Data Sheet

| Conduit Head Glands      |   |
|--------------------------|---|
| PART NUMBER              | CSE-WTF-...   |
| TO SUIT                  | CORRUGATED CONDUIT                                    |
| SUITS CONDUIT SIZE       | 20MM - 50MM   |
| SUITS THREAD SIZE        | M20 - M50   |
| COLOUR                   | BLACK   |
| IP RATING (CABLE/S SEAL) | IP66 & IP67   |
| FIRE RATING (UL 94)      | V2  |
| CRUSH RESISTANCE         | HD  |
| TEMPERATURE RANGE        | -40 TO +100°C   |
| UV PROTECTION            | HIGH  |
| WARRANTY                 | 10 YEARS  |
| REPLACEMENT SCHEDULE     | AT 15 YEARS   |
| BODY MATERIAL            | HIGH UV NYLON   |
| SEAL MATERIAL            | EPDM RUBBER   |
| CONDUIT GRIP RING        | YES   |
| LOCKING GLAND HEAD       | YES   |
| SEALANT REQUIRED         | NO  |
| CUSTOM SIZES AVAILABLE   | YES   |
| LOCKING NUT INCLUDED     | NO (CAN BE SUPPLIED SEPERATELY, OFTEN AT NO COST)     |
| CHEMICAL RESISTANCE      | SALT, WEAK ACID, ALCOHOL, OIL, GREASE & SOME SOLVENTS |

### NOTES