

# RATCHET LOCKING CABLE TIES

## Data Sheet

### SS LOCKING CABLE TIES

PART NUMBER	CSE-SSTIE***-4.5	CSE-LRG-SSTIE350-7	CSE-LRG-SSTIE***-7	CSE-SSTIE***-10
WIDTH	4.5 mm	7 mm	7 mm	10 mm
AVAILABILITY	Made to Order	In Stock	Made to Order	
SOLD PER	Bag			
PACKAGE SIZE (BAG)	100x Ties per bag			
PACKAGE SIZE (CARTON)	Custom	<b>25 Bags (2,500 Ties)</b>		Custom
LENGTH	100 - 500mm	<b>350mm</b>	150 - 800mm	200 - 800mm
BUNDLE DIAMETER RANGE	8 ~ 152mm	<b>24 - 104mm</b>		8 ~ 240mm
INSTALL ON	Static & Tracking Solar, HVAC & Outdoor Use			
SUITS	Solar Cables, TPS, AC Cables, Comms as well as Rigid & Corrugated conduit			
COLOUR	Black			
UV PROTECTION	Extreme			
TENSILE STRENGTH (N.M)	450	700		1,000
TEMPERATURE RANGE	Tie: -60 °C to +550 °C Coating: -40 °C to +150 °C			
FIRE RATING	Not Significantly Flammable			
WARRANTY	15 Years			
MATERIAL (STANDARD)	<b>Tie: SS 316 Coating: Black Oven Cured Proprietary Epoxy</b>			
MATERIAL (CUSTOM)	Tie: SS 201, SS 304 Or SS 316 Coating: With Or Without Black Or Coloured Epoxy			
CUSTOM SIZES AVAILABLE	Yes (See Below)			
RODENT & BIRD PROOF	Yes			
GROUND CONTACT RATED	Yes			
TERMITE RESISTANCE	Yes			
CHEMICAL RESISTANCE	Salt, Acid, Alcohol, Oil, Grease & Some Solvents			
ROHS COMPLIANCE	Yes, Lead Free & Heavy Metals Free			
HALOGEN FREE	Yes			

### SS LOCKING CABLE TIES (SIZES CONTINUED)

	CSE-SSTIE***-4.5	CSE-LRG-SSTIE***-7	CSE-SSTIE***-10
AVAILABILITY	Made to Order		
WIDTH	4.5 mm	7 mm	10 mm
LENGTH:	<b>Bundle Diameter Range:</b>		
100MM	8 - 28mm	n/a	n/a
150mm	8 - 44mm	8 - 42mm	n/a
200mm	20 - 60mm	14 - 58mm	8 - 52mm
250mm	36 - 76mm	30 - 74mm	24 - 74mm
300mm	8 - 88mm	8 - 88mm	8 - 88mm
350mm	24 - 104mm	24 - 104mm	24 - 104mm
400mm	40 - 120mm	40 - 120mm	40 - 120mm
450mm	56 - 136mm	56 - 136mm	56 - 136mm
500mm	72 - 152mm	72 - 152mm	72 - 152mm
800mm	n/a	80 - 240mm	80 - 240mm
Other Sizes can be Custom Manufactured			